

Product Information
High Performance Lubricants

DOW CORNING

Molykote[®] G-2001 High Speed Bearing Grease

FEATURES & BENEFITS

- Wide service temperature range
- Usable for high speeds
- Excellent low temperature properties
- Excellent temperature-consistency profile

COMPOSITION

- Synthetic base oil
- Lithium-calcium thickener
- Corrosion inhibitors

Lithium thickened bearing grease based on synthetic hydrocarbon

APPLICATIONS

- High speed bearings
- Spindles
- Fast moving positioners
- Moulding cutters
- Chemical industry and paper processing

TYPICAL PROPERTIES

Specification Writers: These values are not intended for use in preparing specifications. Please contact your local Dow Corning sales office or your Global Dow Corning Connection before writing specifications on this product.

Test ¹	Property	Unit	Result
	Color		Beige
	Base oil type		PAO
	Thickener type		Lithium-calcium soap
	Consistency, Viscosity		
DIN 51 818	Consistency	NLGI Class	2
ISO 2137	Worked penetration	mm/10	265 - 295
DIN 51 562	Base oil viscosity at 40°C	mm ² /s	35
DIN 51 562	Base oil viscosity at 100°C	mm ² /s	6
	Temperature		
	Service temperature range	°C	-50 to +130
		°F	-58 to +266
ISO 2176	Drop point	°C (°F)	>190 (>374)
DIN 51 805	Flow pressure at -35°C	mbar (psi)	450 (6.5)
DIN 51 805	Flow pressure at -50°C	mbar	<1400 (<20.3)
	Low Temperature Torque		
ASTM D 1478-63	at -20 starting / running	Nm x 10 ⁻³	53 / 53
	at -20 starting / running	Nm x 10 ⁻³	106 / 106
	Oil Separation		
DIN 51 817	Oil Separation (18hrs/40°C)	Mass-%	<2.5
	Evaporation loss (30 hrs/ 100°C)	Mass-%	0.6
DIN 51 808	Oxidation stability, pressure drop (100 hrs / 99°C)	bar	<0.8
	Load Carrying Capacity, Wear Protection, Speed		
DIN 51 821-1	FE9 (6000 rpm / 1500N/ 130°C)	F ₅₀ [hrs]	175
DIN 51 350-4	Four Ball Tester Weld load	N	1500
DIN 51 350	Wear Scar under 400N load	mm	0.69
	DN value (D _R x rpm)		900,000
DIN 51 802	SKF EMCOR		0 - 0
ASTM D 4048	Copper Corrosion (24 hrs / 100°C)	Level	1

¹DIN: Deutsche Industrie Norm.

ISO: International Standardization Organization.

ASTM: American Society for Testing and Materials.

DESCRIPTION

Molykote[®] G-2001 High Speed Bearing Grease is a synthetic oil-based grease thickened by a lithium-calcium system. *Molykote* G -2001 Grease offers excellent low temperature performance. *Molykote* G -2001 Grease provides premium protection against wear and corrosion. The absence of solid lubricants makes *Molykote* G -2001 Grease well suited for small to medium sized rolling element bearings at high speeds.

HOW TO USE

Apply using conventional grease application methods, i.e., clean brush, grease gun and manual or automated dispensing equipment.

HANDLING

PRECAUTIONS

PRODUCT SAFETY

INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND MATERIAL SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE MATERIAL SAFETY DATA SHEET IS AVAILABLE ON THE DOW CORNING WEB SITE AT DOW CORNING.COM, OR FROM YOUR DOW CORNING SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CORNING CUSTOMER SERVICE.

USABLE LIFE AND STORAGE

When stored between 0 and 40°C in the original unopened containers, this product has a usable life of 60 months from the date of production.

PACKAGING INFORMATION

This product is available in different standard container sizes. Detailed container size information should be obtained from your nearest Dow Corning sales office or Dow Corning distributor.

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

HEALTH AND ENVIRONMENTAL INFORMATION

To support Customers in their product safety needs, Dow Corning has an extensive Product Stewardship organization and a team of Product Safety and Regulatory Compliance (PS&RC) specialists available in each area.

For further information, please see our Website, dowcorning.com or consult your local Dow Corning representative.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow Corning's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

DOW CORNING SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

We help you invent the future.[™]

molykote.com