

MOLYKOTE® L 13 Thinner

Solvent-based thinner

Features

- Transparent
- No intentional polytetrafluoroethylene (PTFE) or per- and polyfluoroalkyl substances (PFAS)

Composition

- Mix of organic solvents

Applications

Diluting and cleaning solvent for specific solvent-based MOLYKOTE® Anti-Friction Coatings. Especially for products like MOLYKOTE® D 321 R Anti-Friction Coating, MOLYKOTE® D 3484 Anti-Friction Coating, MOLYKOTE® 3400A Anti-Friction Coating LF, MOLYKOTE® 3402-C LF Anti-Friction Coating, MOLYKOTE® 106 Anti-Friction Coating, MOLYKOTE® PTFE-N UV Anti-Friction Coating, and MOLYKOTE® D 708 Anti-Friction Coating.

How to use

Stir thoroughly before applying the diluted product.

Handling precautions

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION.

Usable life and storage

When stored between 0°C and 40°C in the original unopened containers, MOLYKOTE® L 13 Thinner has a usable life of 60 months from the date of production.

Packaging

This product is available in different standard container sizes as shown on molykote.com. Detailed container size information should be obtained from your nearest MOLYKOTE® sales office or MOLYKOTE® distributor.

Typical properties

Specification writers: These values are not intended for use in preparing specifications. Please contact your local MOLYKOTE® sales representative prior to writing specifications on this product.

Standard ⁽¹⁾	Test	Unit	Result
	Color		Transparent
Physical properties			
DIN 53217/2	Density at 20°C	g/ml	0.85
DIN EN 456	Flash point (closed cup)	°C	27
	Storage life	years	5

⁽¹⁾DIN: Deutsche Industrie Norm.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.
© 1998-2024 DuPont.

The information set forth herein is furnished free of charge and is based on technical data that DuPont believes to be reliable and falls within the normal range of properties. It is intended for use by persons having technical skill, at their own discretion and risk. This data should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents.